

# Treff Vial HP

(Transport and Autosampler Vial)





CleanRoom®  
**PURE**

The Treff Vial HP with septum cap is specially designed to meet required parameters of modern transport and autosampler vials.

## General Characteristics – Treff Vial HP

---

Thanks to its special design and 2K material combination it is capable of withstanding up to 5 bar internal pressure and has a 2 bar resealing tightness after needle penetration of the septum. Its outstanding DMSO tightness makes the Treff Vial HP to an ideal storage and transport vessel for a wide range of research, development, quality control and production laboratories. Each vial features an individual unique 2D tube number to ensure retraceability at any time.

### **All TreffLab Vial HP feature the following characteristics:**

- › Outstanding dynamic transport tightness and resealing properties
- › Autosampler and transport system approved
- › 100% virgin medical-grade PP only, no additives, providing high chemical quality
- › Microbiological controlled production in cleanrooms class 8, ISO 14644-1
- › Free of RNase, DNase, human DNA, endotoxins, PCR inhibitors and ATP
- › Capacity: up to 350 µl
- › Up to 5 bar / 72.5 psi internal pressure tightness
- › Resealing tightness after needle penetration of septum: 2 bar / 29 psi
- › Temperature range: - 80°C up to 100°C
- › Ready to Use (CleanRoom Pure®)

## Treff Vial HP 350 µl *transport and autosampler vial*

- ▶ Leak safe sample transport vessel for fully automated delivery systems
- ▶ Individual unique 2D barcode



1

Product Description	Material	Color	Quantity	Order No.	Image No.
Treff Vial HP 350 µl	PP	clear	<b>5'000</b> 10 bags of 500 Tubes 10 bags of 500 Caps	96.11418.9.00	1



## **Nolato Treff AG**

---

Taastrasse 16, 9113 Degersheim

Switzerland

Phone: +41 71 372 55 55

E-Mail: [treff.ag@nolato.com](mailto:treff.ag@nolato.com), [trefflab@nolato.com](mailto:trefflab@nolato.com)

[www.nolato.com/treff](http://www.nolato.com/treff)

[www.trefflab.com](http://www.trefflab.com)